

RIPS-Hurricane RP3000

Inert Gas Purge LoadPort

First in the world,

The Inert Gas Purge LoadPort which makes it possible to jet into all FOUPs, and it is compliance with SEMI Standard.

Features

*** All kinds of FOUP**

This type can jet into all FOUPs.
(Inert gas is not infected from purge-port.)

*** Max 200LPM Jet**

After the FOUP door is opened, inert gas is jetted in from the door side.
(Max 200LPM)

*** N2 Purge time sharply**

The substitution time is greatly shortened by throwing a large amount of inert gas at a dash, and the gas gross weight is decreased too.

*** SEMI**

This type is compliance with SEMI Standard.
(SEMI Standard E63 y74=100mm)



Type	RP3000	
Wafer Size	300 mm	
Outline	Height	1376 mm
	Depth	590 mm (SEMI Standard E63 y74=100mm included)
	Width	475 mm
	Weight	92 kg
Utility	Power	24 VDC (+/-5%), 5A (During Cycle)
	Vacuum	-60 kPa minimum (5L / min minimum)
	N2 Gas	0.7~1.0MPa
Communications	Serial RS-232C (ASCII)	

RIGHT MFG. CO., LTD

1-47-3, Maeno-cho, Itabashi-ku, Tokyo, 174-8633 Japan.
TEL. 03-3960-2246 Fax. 03-3960-2620
URL. <http://www.rightmfg.co.jp>

ISO 9001
BUREAU VERITAS
Certification

